

Comment	Description	Designator	Footprint	LibRef	Quantity
1729128	PCB Terminal Block, 13.5 A, 400 V, 2-Pin THD, RoHS, Bulk	1_Led1, 1_Led2, 1_Led3, 1_Led4, 1_Led5, 1_Led6, 1_Led7, 1_Led8, 1_Led9, 1_Led10, 2	PHOE-1729128-2_V	CMP-2000-05815-1	11
approved sub OK	Capacitor SMD Cer 2.2uF 10% 16V X7R 0805	C1_Led1, C1_Led2, C1_Led3, C1_Led4, C1_Led5, C1_Led6, C1_Led7, C1_Led8, C1_Led9, C1_Led10, C2_Led1, C2_Led2, C2_Led3, C2_Led4, C2_Led5, C2_Led6, C2_Led7, C2_Led8, C2_Led9, C2_Led10	CAPC2012X135N	CAPC_2u2_0805	20
1N5819HW-7-F	DIODE SCHOTTKY 40V 1A SOD123	D1_Led1, D1_Led2, D1_Led3, D1_Led4, D1_Led5, D1_Led6, D1_Led7, D1_Led8, D1_Led9, D1_Led10	FP-SOD123-IPC_A	CMP-0303-00003-2	10
IHLP4040DZER330M1A	Automotive Inductors, Low DCR Series 33uH 4.4A 94.5mΩ 20%	L1_Led1, L1_Led2, L1_Led3, L1_Led4, L1_Led5, L1_Led6, L1_Led7, L1_Led8, L1_Led9, L1_Led10	FP-IHLP-4040DZ-FP_3_124x3-MFG	CMP-02424-000365-1	10
Header 10X2	Header, 10-Pin, Dual row	P1	HDR2X10	Header 10X2	1
PT4115	30V, 1.2A Step-down Hlgh Brightness LED Driver with 5000:1 Dimming	PT_Led1, PT_Led2, PT_Led3, PT_Led4, PT_Led5, PT_Led6, PT_Led7, PT_Led8, PT_Led9, PT_Led10	SOT-89-5	PT4115	10
Thick Film	Resistor SMD chip 0.0 Ohm 0.25W 1206	R1_Led1, R1_Led2, R1_Led3, R1_Led4, R1_Led5, R1_Led6, R1_Led7, R1_Led8, R1_Led9, R1_Led10	RESC3216N_ZERO	RES_0R_1206	10